



# TEXRECO CONTRACT EXTRA CLEAR



TRANSPARENT PASTE  
ADHESIVE FOR COMMERCIAL  
AND CONTRACT FABRIC  
WALL COVERINGS

TECHNICAL DATA SHEET UPDATED 18/02/2026

---

## Product Information

Ready-to-use TRANSPARENT paste adhesive for commercial and contract fabric wall coverings.

- + High resistance
- + Does not stain, even on dark wallcoverings
- + High yield
- + Low VOC (Volatile Organic Compounds)



- 
- All types of residential and contract wallcoverings with non-woven fabric backing
  - Fiberglass wallcoverings
  - Dark and embossed wallpapers
  - Fabric wallcoverings

---

## Coverage

150 - 250 g/m<sup>2</sup>

---

## Application Instructions

### Substrate Preparation

All substrates must be dry, absorbent, sound, and free from dust, paint, or oils. Any cracks or holes should be repaired with our lightweight filler GLASTER and, if needed, leveled with standard gypsum filler. We recommend using PRIMER AC for consolidation and cleaning, and PRIMER SP for damp walls, as it is specifically formulated to combat mold and bacteria.

---

### Product preparation

The product is ready to use; if needed, dilute with up to 5–10% clean water.

---

### Product application

Apply the adhesive directly to the back of the wallpaper or onto the wall, following the manufacturer's instructions.

---

### Cleaning

Remove any excess adhesive from joints with a damp sponge. THE PRODUCT DOES NOT STAIN.

---



# TEXRECO CONTRACT EXTRA CLEAR



TRANSPARENT PASTE  
ADHESIVE FOR COMMERCIAL  
AND CONTRACT FABRIC  
WALL COVERINGS

TECHNICAL DATA SHEET UPDATED 18/02/2026

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	10004-C-EC-2-N	5	kg	Rectangular Bucket	2
	10005-C-EC-N	10	kg	Rectangular Bucket	-
	10006-C-EC-N	15	kg	Rectangular Bucket	-

Technical Data	Base	Starch
	Physical appearance	Semi-transparent cream
	pH	6.5
	Viscosity	50,000–60,000 cps
	VOC	<0.005 mg/m <sup>3</sup>
	Solids content	Approx. 35%
	Customs code	3505 2010
	Application temperature	+5 °C to +40 °C
	Waiting time	0–10 minutes
	Open time	20–30 minutes
	Complete drying	48 hours

## Warnings

The product should not be applied to non-absorbent, damaged, or moist surfaces.

## Storage

The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date.  
It is essential to store the product in a dry place, away from heat sources and direct sunlight.



# TEXRECO CONTRACT EXTRA CLEAR

---



TRANSPARENT PASTE  
ADHESIVE FOR COMMERCIAL  
AND CONTRACT FABRIC  
WALL COVERINGS

TECHNICAL DATA SHEET UPDATED 18/02/2026

---

**Final note**

Keep out of the reach of children and pets.  
Dispose of waste in designated containers for construction materials.

---

**Disclaimer**

The information in this technical sheet is based on our long-standing experience but is provided as a guideline.

The user is responsible for determining whether the product is suitable for their specific application and for its use.

---